



# TECHNICAL DATASHEET Coverfit

### **FEAUTRES**

- » Polycarobonate frame.
- » 2.5 base curve polycarbonate lens with 99.9% UV protection.
- » Co-mold adjastable metal core temple.
- » Soft nose pads.
- » OTG
- » Frame width: 156 mm
- » Coating: Clear.
- » AntiScratch and AntiFog.
















## WEIGHT

» 44 g.

### **PACKAGING**

Per Box 12 pairsPer Carton 25 boxes

#### **CLEANING AND STORAGE**

Cleaning: The lenses should be cleaned regularly.

» Maintenance: Pitted, scratched or damaged lenses must be


replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre

pouch or rigid case.

» Storage: All products must be stored in a dry and clean

environment.





VERSIONS	AMBER •	INDOOR/OUTDOOR
FRAME MARKING	EN166 FT CE / ANSI	EN166 FT CE / ANSI
PROTECTION AGAINST	Impacts, UV radiations	Impacts, UV radiations
COATINGS	K&N Anti-scratc Anti-fog / UV400 / Moisture repellent	Mirror Coating Moisture Repellent Anti-fog on inside



# TECHNICAL DATASHEET Coverfit

- (P) AUSTRALIA SYDNEY
- +61 415 251 119
- (V) UAE DUBAI
- +971 503 242 474
- www.aragoon.com.au
- (@) info@aragoon.com.au